

UVS-Y YÜKSEK BASINÇLI RADYAL FAN UVS-Y HIGH PRESSURE RADIAL FAN



KULLANIM ALANLARI / AREAS OF USAGE



- Toz toplama / Collecting dust
- Duman ve egzost tahliyesinde / Fume-gas elimination
- İnce tanecikli malzeme naklinde (mermer tozu, tahta tozu, granür, plastic vs.) / (marble dust, granule etc.)
- Matbaalarda, kağıt, mobilya, kereste, suntan, seramik ve mermer fabrikalarında / At printing houses, different factories.

ÖZELLİKLERİ / SPECIFICATIONS

- Debi / Airflow : 6500 – 22500 m³/h
- Basınç / Pressure : 2800 - 4250 pa
- Direkt akuple veya kayış kasnak tahrikli / Direct coupling or belt driven



MODEL	VOLTAJ (V)	FREKANS (Hz)	AKIM (A)	POWER (kW)	RPM (d/d)	AIRFLOW (Debi) (m ³ /h)	PRESSURE (Basınç) (Pa)	KORUMA SINIFI (IP)
UVS-Y10	380	50	12,7	7.5	2800	6500	2800	55
UVS-Y15	380	50	20,8	11	2800	8500	3000	55
UVS-Y20	380	50	27,8	15	2800	10000	3500	55
UVS-Y25	380	50	34,4	18.5	2800	12500	3700	55
UVS-Y30	380	50	41,8	22	2800	15000	4000	55
UVS-Y40	380	50	58,7	30	2800	20000	4150	55
UVS-Y50	380	50	68.4	37	2800	22500	4250	55



MODEL	A	B	C	D	FØ
UVS-Y10	950	735	275	340	300
UVS-Y15	1020	785	295	380	300
UVS-Y20	1130	850	345	420	395
UVS-Y25	1195	890	390	460	395
UVS-Y30	1195	890	390	460	395
UVS-Y40	1255	950	390	490	415
UVS-Y50	1320	1010	410	520	425

All dimensions are in mm.